



Specifications

Reikken Model	Nominal Voltage	Continuous Wattage	Weight lbs.	Capacity Ah	Group Size	Positive Term
RE620	12	650	12	18	-	R
RE720	12	750	13	20	-	R
RE820	12	850	24	35	U-1	L
RE1220	12	1200	28	50	-	R
RE1420	12	1400	34	55	22/51	L
RE1820	12	1800	48	75	24	L
RE2020	12	2000	57	90	27	L
RE2420	12	2400	66	110	31	L
HO3229	12	3200	70	120	31	L
RE-Reikken	12	5200	123	200	-	R
RE34UH	12	na	42	70	34	L

Reikken Model	Power Cell Dimensions					
	Inches			Millimeters		
	L	W	H	L	W	H
RE620	7.13	3.00	6.54	181	76	165
RE720	7.13	3.03	6.57	181	77	166
RE820	7.75	5.11	6.25	197	130	159
RE1220	7.76	6.54	6.86	197	166	174
RE1420	9.02	5.43	8.27	229	138	210
RE1820	10.24	6.66	8.31	260	169	211
RE2020	12.10	6.66	8.31	307	169	211
RE2420	13.04	6.82	8.39	331	173	213
HO3220	13.00	6.73	8.66	330	171	220
RE-Reikken	20.57	9.46	8.51	522	240	216
RE34UH	10.24	6.61	7.20	260	168	183

Specifications are subject to change without notice. Reikken makes no representation or warranty whatsoever regarding the completeness, accuracy, up to date state, or adequacy of, or the suitability, functionality, availability, or operation of the information or materials it contains and the eventuality(s), probability(s) and possibility (s) might prevail whereby information featured onto The web site or printed materials may contain technical inaccuracies, grammatical errors, typographical errors, source-data errors, misprints or omissions, out of date information, technical or quote inaccuracies.